



ROLLING SHUTTERS • INDUSTRIAL DOORS



- Durability
- Safety
- High Performance
- Low Maintenance
- Thermal Isolation
- Motors & Automation
- Diversity of Models
- High-end Finishing

FA 100

ROLLING SHUTTERS • INDUSTRIAL DOORS

أبواب لفافة محسنة بفوم كثافة عالية

Roller shutter made of:


- a) pre-painted aluminum panel, 0,5mm thick and 100mm wide or
- b) steel, 0,5mm thick and 100mm wide.

The interior consists of ecological polyurethane, thickness 17mm, density 160kg/m², thermal resistance rate 4,8 W/(m²·K).

It combines high strength and security standards, low noise during operation, thermal insulation, sound insulation and perfect finishing.

Type FA 100 is delivered electrostatically painted in the shades of the main color index, even in wood imitation.

PROFILE A:
ALUMINUM
DIMENSION:
100mm
THICKNESS:
0,5mm



PROFILE B:
STEEL
DIMENSION:
100mm
THICKNESS:
0,5mm



Special polyamide cap at profile ends that reduces friction and noise.



Ability to incorporate special glazing made of transparent plastic material for lighting and visual communication with the interior.



الفجر الجديد

Amman - Jordan

Tel . + 962 6 4163020 - Fax : + 962 6 4160134
www.al-fajergroup.com

*ALFAJER LTD RESERVES THE RIGHT TO CHANGE THE MAIN COLOR INDEX.
*SHADE ILLUSTRATION IS INDICATIVE.