

# SEKUR FT

## PHOTOCELLS



FT33



FT23



FT43



FT43B

		FT33	FT23	FT43	FT43B
<b>ELECTRICAL DATA</b>					
power	Vac	10-30	10-30	10-30	10-30
	Vdc	10-40	10-40	10-40	10-40
range	m	25	25	25	20
consumption rx	mA	27	27	27	35
consumption tx	mA	10	10	10	0,04
relay contacts max supply	A	1	1	1	1
<b>GENERIC DATA</b>					
protection degree	IP	54	54	54	54
dimensions (L - P - H)	mm	80 - 33 - 88	30 - 26 - 88	38 - 38 - 109	38 - 38 - 109
operating temperature	°C	-20 + 55	-20 + 55	-20 + 55	-20 + 55

## PLUS

New logic circuit with improved performance

Snow function: photocell activates an adaptatively temporized mode, in case of frequent dimming or

darkening, to avoid false obstacles detection

Two programmable ranges

## MODELS

CODE	DESCRIPTION
FT33	Pair of photocells for external use and flush mounting
FT23	Pair of photocells for external use for small pillars
FT43	Pair of photocells for external use adjustable through 180°, for small pillars
FT43B	Pair of photocells for external use adjustable through 180°, for small pillars, battery powered

## ACCESSORIES



**MUR-P**  
Plastic wall  
support for FT33